

Revised 70

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : Perkote 40-264
 IDENTIFICATION NUMBER: 46260
 PRODUCT USE/CLASS : Rust Preventive

DATE PRINTED: 07/25/01

SUPPLIER: PERKINS PRODUCTS INC. 7025 WEST 66TH PLACE BEDFORD PARK, IL 60638	MANUFACTURER: PERKINS PRODUCTS INC. 7025 WEST 66TH PLACE BEDFORD PARK, IL 60638
EMERGENCY TELEPHONE: 800-424-9300 Chemtrec---24 Hours	EMERGENCY TELEPHONE: 800-424-9300 Chemtrec---24 Hours

PREPARER: William L. Fanning, PHONE: 708-458-2000, PREPARE DATE: 01/24/95

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % LESS THAN	ACGIH TLV-TWA	OSHA TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	SKIN
Paraffinic distillates light	00064742-55-8	90.0 %	5mg/m3 (mist)	N.E.	5mg/m3 (mist)	N.E.	NO

SECTION 3 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: No Information.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: This material is not expected to be irritating to the eyes. However if direct eye contact should occur, flush with water for 15 minutes. If irritation should develop and persist then consult a physician.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Not expected to be a skin irritant, however it may cause irritation or dermatitis in some individuals upon prolonged contact.

EFFECTS OF OVEREXPOSURE - INHALATION: This material has a low vapor pressure and is not expected to present an inhalation hazard. However, if

(Continued on Page 2)

Product: 46260

Preparation Date: 01/24/95

Page 2

SECTION 3 - HAZARDS IDENTIFICATION

the TLV of 5 mg/m³ is exceeded then inhalation of mists or vapors may cause a mild irritation of the mucous membranes of the upper respiratory tract.

EFFECTS OF OVEREXPOSURE - INGESTION: No hazard in normal industrial use.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information.

PRIMARY ROUTE(S) OF ENTRY: INHALATION

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air.

FIRST AID - INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 265 F
(CLEVELAND OPEN CUP)

LOWER EXPLOSIVE LIMIT: 0.9 %
UPPER EXPLOSIVE LIMIT: 7.0 %

AUTOIGNITION TEMPERATURE: N.A.

EXTINGUISHING MEDIA: CO₂ DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Water runoff can cause environmental damage. Dike and collect water used to fight fire.

(Continued on Page 3)

Product: 46260

Preparation Date: 01/24/95

Page 3

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE

HANDLING: No special handling techniques required. See Sections 6,8 and 10.

STORAGE: Keep away from heat, sparks and flame.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: No Information.

EYE PROTECTION: No Information.

OTHER PROTECTIVE EQUIPMENT: No Information.

HYGIENIC PRACTICES: Wash hands before eating. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 450 - 450 F
 ODOR : Low odor
 APPEARANCE : Clear amber
 SOLUBILITY IN H2O : Insoluble
 FREEZE POINT :
 VAPOR PRESSURE : 15mm Hg

VAPOR DENSITY : Is heavier than air
 ODOR THRESHOLD : N.A.
 EVAPORATION RATE: Is slower than Butyl Acetate
 SPECIFIC GRAVITY: 0.8309
 pH @ 0.0 % : N.A.

(Continued on Page 4)

Product: 46260

Preparation Date: 01/24/95

Page 5

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: PETROLEUM LUBE OIL NOIBN

DOT TECHNICAL NAME: NON HAZARDOUS SHIPMENT

DOT HAZARD CLASS:

HAZARD SUBCLASS:

DOT UN/NA NUMBER:

PACKING GROUP:

RESP. GUIDE PAGE:

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Jone

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN
No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER
No information is available.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

(Continued on Page 6)

Product: 46260

Preparation Date: 01/24/95

Page 6

SECTION 15 - REGULATORY INFORMATION

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 01/06/94

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.00 lbs/gal, 0 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

<END OF MSDS>